

(12) PATENT  
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199916647 B2  
(10) Patent No. 742771

(54) Title  
Conductive organic coatings

(51)<sup>6</sup> International Patent Classification(s)  
C09D 005/10 C09D 163/00

(21) Application No: 199916647 (22) Application Date: 1998 .10 .28

(87) WIPO No: W099/24515

(30) Priority Data

(31) Number (32) Date (33) Country  
19748764 1997 .11 .05 DE

(43) Publication Date : 1999 .05 .31  
(43) Publication Journal Date : 1999 .07 .29  
(44) Accepted Journal Date : 2002 .01 .10

(71) Applicant(s)  
Henkel Kommanditgesellschaft auf Aktien

(72) Inventor(s)  
Winfried Wichelhaus; Wolfgang Lorenz; Andreas Kunz; Wolfgang Krey

(74) Agent/Attorney  
SPRUSON and FERGUSON,GPO Box 3898,SYDNEY NSW 2001

(56) Related Art  
US 5429880  
US 4748194  
WO 94/09051

BEST AVAILABLE COPY

16647/99

PCT

WELTORGANISATION FÜR GEISTIGES EIGENTUM  
Internationales BüroINTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE  
INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)

(51) Internationale Patentklassifikation <sup>6</sup> : C09D 5/10, 163/00	A1	(11) Internationale Veröffentlichungsnummer: WO 99/24515 (43) Internationales Veröffentlichungsdatum: 20. Mai 1999 (20.05.99)
(21) Internationales Aktenzeichen: PCT/EP98/06824 (22) Internationales Anmeldedatum: 28. Oktober 1998 (28.10.98) (30) Prioritätsdaten: 197 48 764.5      5. November 1997 (05.11.97)      DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): HENKEL KOMMANDITGESELLSCHAFT AUF AKTIEN (DE/DE); Henkelstrasse 67, D-40589 Düsseldorf (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): WICHELHAUS, Winfried (DE/DE); Stifterstrasse 3, D-40822 Mettmann (DE). LORENZ, Wolfgang (DE/DE); Amschweg 11, D-40699 Erkrath (DE). KUNZ, Andreas (DE/DE); Birgdenier Berg 15b, D-42855 Remscheid (DE). KREY, Wolfgang (DE/DE); Moospfad 17, D-42113 Wuppertal (DE).	(81) Bestimmungsstaaten: AU, BG, BR, BY, CA, CN, CZ, GE, HU, ID, IS, JP, KG, KP, KR, KZ, LK, LT, LV, MD, MX, NO, NZ, PL, RO, RU, SG, SI, SK, TJ, TM, TR, UA, US, UZ, VN, YU, europäisches Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, L <sup>1</sup> , MC, NL, PT, SE). Veröffentlicht Mit internationalem Recherchenbericht. Vor Ablauf der für Änderungen der Ansprüche zugelassenen Frist; Veröffentlichung wird wiederholt, falls Änderungen eintreffen.	
(54) Title: CONDUCTIVE ORGANIC COATINGS (54) Bezeichnung: LEITFÄHIGE, ORGANISCHE BESCHICHTUNGEN (57) Abstract <p>The invention relates to conductive, weldable anti-corrosion compositions with a base consisting of (blocked) polyurethane resins, epoxide resins and nitrogenous resins and conductive fillers. The inventive compositions are suitable for coating metal surfaces, especially steel sheets, using the coil-coating technique, and are characterised by a low burning-in temperature, by a significant reduction of white rust on galvanised sheet steel in the salt spray test and in that the organic coating adheres better to the metallic substrate. These coatings also provide adequate protection against corrosion even with low chrome plating, preferably also with Cr-free pre-processing techniques. Sheets coated in this way can be spot-welded using any conventional technique.</p> (57) Zusammenfassung <p>Leitfähige und schweißbare Korrosionsschutz-Zusammensetzungen auf der Basis von (blockierten) Polyurethanharzen, Epoxidharzen sowie stickstoffhaltigen Härtern und leitfähigen Füllstoffen eignen sich zur Beschichtung von Metalloberflächen, insbesondere Stahlblechen im Coil-Coatingverfahren. Diese Zusammensetzungen zeichnen sich durch eine niedrige Einbrenntemperatur, eine deutliche Reduzierung des Weißrostes auf verzinktem Stahlblech im Salzprühtest sowie durch eine Verbesserung der Haftung der organischen Beschichtung auf dem metallischen Substrat aus. Weiterhin bewirken diese Beschichtungen einen ausreichenden Korrosionsschutz auch bei niedriger Chrom-Auflage, vorzugsweise auch bei Cr-freien Vorbehandlungs-Verfahren. Derartig beschichtete Bleche können mit allen herkömmlichen Verfahren punktgeschweißt werden.</p>		

IP AUSTRALIA

31 MAY 1999

RECEIVED

## Conductive Organic Coatings

This invention relates to conductive and weldable anti-corrosive compositions for coating metal surfaces and to a process for coating metal surfaces with electrically conductive organic coatings.

In the metals processing industry, in particular in automotive construction, the metallic components of the products must be protected from corrosion. According to the conventional prior art, this is achieved by initially coating the sheet metal in the rolling mill with anti-corrosive oils and optionally with drawing greases before forming and stamping. In automotive construction, sheet metal components appropriately formed for bodywork or bodywork components are stamped out and formed by deep drawing using such drawing greases or oils and then generally joined together by welding and/or crimping and/or adhesive bonding and then elaborately cleaned. Anti-corrosive surface pretreatment, such as phosphating and/or chromating, is then performed, whereupon a first lacquer layer is applied onto the components by electrocoating. Especially in the case of automotive bodywork, this first electrocoating is followed by the application of further lacquer layers.

There is a need to find simpler production processes which make it possible to weld already precoated sheet metal and to electrocoat it in a proven manner. There is thus a range of processes in which, after phosphating and/or chromating, an organic coating which is conductive to a greater or lesser degree is applied in the so-called coil coating process. These organic coatings should generally be of a composition such that they have sufficient electrical conductivity not to impair the electrical spot welding process. It should moreover be possible to coat these coatings with conventional electrocoating lacquers. It should furthermore be possible to stamp and form the sheet metal coated in this manner with reduced usage of deep drawing greases or oils. Recently, especially in the automotive industry, galvanised and/or alloy-galvanised sheet steel and aluminium and magnesium sheet have increasingly been used in addition to standard sheet steel.

It is in principle known to coat sheet steel with organic coatings which are weldable and are applied directly in the rolling mill using the so-called coil coating process.

DE-C-3412234 thus describes a non-blocking and weldable anti-corrosive primer for electrolytically thin galvanised, phosphated or chromated and formable sheet steel. This anti-corrosive primer consists of a mixture of over 60% zinc, aluminium, graphite and/or molybdenum disulfide and another anti-corrosive pigment and 33 to 35% of an organic binder, together with about 2% of a dispersion auxiliary or catalyst. Polyester resins and/or epoxy resins and derivatives thereof are proposed as the organic binder. It is assumed that this technology forms the basis of the coating composition known in the industry under the name "Bonazinc 2000". Although this process offers some advantages in comparison with the above-stated method (temporary corrosion protection with anti-corrosive oils, followed by subsequent degreasing once the metal components have been joined), the process described in DE-C-3412234 is still in great need of improvement:

- this coating is not sufficiently spot weldable
- the stoving temperature for such coatings at a peak metal temperature (PMT) of 250 to 260°C is still too high. Many recent steels with the "bake-hardening" effect cannot be used at such high stoving temperatures.



- lacquer adhesion onto the pretreated substrates, preferably galvanised steels, is still inadequate, especially if the sheets are subjected to relatively severe forming in the press.

According to the teaching of DE-C-3412234, the organic binder may consist of polyester resins and/or epoxy resins and derivatives thereof. An epoxy/phenyl precondensate, an epoxy ester and linear, oil-free terephthalic acid based copolyesters are explicitly mentioned.

EP-A-573015 describes organically-coated composite sheet steel consisting of a surface coated on one or two sides with zinc or zinc alloy, which surface is provided with a chromate film and, thereon, an organic coating having a film thickness of 0.1 to 5µm. The organic coating is formed from a primer composition consisting of an organic solvent, an epoxy resin having a molecular weight of between 500 and 10000, an aromatic polyamine and a phenol or cresol compound as accelerator. The primer composition furthermore contains a polyisocyanate and colloidal silica. According to this document, the organic coating is preferably applied to a dry film thickness of 0.6 to 1.6µm as layers thinner than 0.1µm are too thin to provide corrosion protection. Film thicknesses of above 5µm, however, impair weldability. DE-A-3640662 similarly describes surface treated sheet steel comprising sheet steel provided with coating of zinc or zinc alloy, a chromate film formed on the surface of the sheet steel and a layer of a resin composition formed on the chromate film. This resin composition consists of a basic resin, which is produced by reacting an epoxy resin with amines, together with a polyisocyanate compound. This film too may only be applied to dry film thicknesses of less than about 3.5µm as weldability is severely reduced at greater film thicknesses.

EP-A-380024 describes organic coating materials based on a bisphenol A type epoxy resin having a molecular weight of between 300 and 100000, together with a polyisocyanate or blocked polyisocyanate, pyrogenic silica and at least one organic colouring pigment. In this process too, pretreatment with chromate to form a thick Cr coating is required. The organic layer cannot be thicker than 2µm as sheets having thicker organic coats cannot satisfactorily be spot welded and the properties of the electrocoating lacquer applied onto the organic coating are degraded.

An object thus arose of providing coating compositions which satisfy the automotive industry's requirements in all respects. In comparison with the prior art, it is intended to improve the following properties of the organic coating compositions suitable for the coil coating process:

- lower stoving temperature, preferably no higher than 210 to 235°C PMT
- distinct reduction in white rust on galvanised sheet steel in the salt spray test to DIN 50021, ie. better corrosion protection
- improvement in adhesion of the organic coating on the metallic substrate assessed by the T-bend test (ECCA standard) and impact test (ECCA standard)
- sufficient corrosion protection even with a thin Cr coating, preferably using Cr-free pretreatment methods
- cavity sealing with wax or products containing waxes, which is still conventional, should become superfluous thanks to the improved corrosion protection
- suitability for spot welding.

The invention provides a conductive and weldable anti-corrosive coating composition for coating metal surfaces, comprising: (a) 10 to 40wt% of an organic binder containing: (aa) at least one



epoxy resin; (ab) at least one curing agent selected from guanidine, substituted guanidines, substituted ureas, melamine resins, guanamine derivatives, cyclic tertiary amines and mixtures thereof; (ac) at least one blocked polyurethane resin; (b) 0 to 15wt% of a silicate-based anti-corrosive pigment; (c) 40 to 70wt% of powdered zinc, aluminium, graphite, molybdenum disulfide, carbon black, iron phosphide, and/or barium sulfate doped with tin or antimony; (d) 0 to 30wt% of a solvent.

The solution according to the present invention also comprises the use of the above-stated composition for coating sheet metal in the coil coating process.

The solution according to the present invention furthermore comprises a process for coating metal surfaces with a conductive organic anti-corrosive layer characterised by the following stages:

- 10   ▪ conventional pretreatment consisting of
  - cleaning
  - optionally phosphating
  - chromating
  - optionally chromium-free pretreatment
- 15   ▪ coating with a composition of the above-stated type to a film thickness of 1 to 10µm, preferably of between 2 and 5µm
- stoving of the organic coating at temperatures of between 160°C and 260°C peak metal temperature (PMT).

The metal surfaces to be coated according to the present invention are preferably iron (sheet steel), galvanised and alloy-galvanised steels, aluminium or magnesium.

For the purposes of the present invention, an electrically conductive coating should be taken to mean one which is weldable under joining conditions conventional in the automotive industry, preferably using the spot welding process. These coatings furthermore have sufficient conductivity to ensure complete deposition of electrocoating lacquers.

25   The epoxy resin is an essential constituent of the organic binder of the anti-corrosive composition according to the present invention. An epoxy resin or a blend of two or more epoxy resins may be used here. The epoxy resin or resins may have a molecular weight of between 300 and 100 000, with epoxy resins having at least two epoxy groups per molecule and a molecular weight of above 700 preferably being used, as experience has shown the higher molecular weight epoxies to give rise to no occupational hygiene problems during application. Numerous epoxy resins may in principle be used, such as the glycidyl ethers of bisphenol A or the glycidyl ethers of novolac resins. Examples of the first-stated type are commercially available under the trade names "Epicote 1001", "Epicote 1004", "Epicote 1007" and "Epicote 1009" from Shell Chemie. Numerous other conventional commercial epoxy resins of the bisphenol A glycidyl ether type may also be used, as well as the above-stated epoxy resins.

Examples of novolac epoxy resins are the "Araldite" ECN grades from Ciba Geigy, DEN grades from Dow Chemical and numerous other manufacturers.

Polyesters bearing epoxy groups, which also includes the epoxy derivatives of dimeric fatty acids, may also be used as an epoxy resin binder component.



These epoxy resins to be used according to the present invention are preferably solid in the solvent-free state at room temperature; during production of the composition, they are used as a solution in an organic solvent.

The curing agent or agents for the organic binder may be guanidine, substituted guanidines, substituted ureas, melamine resins, guanamine derivatives, cyclic tertiary amines, aromatic amines and mixtures thereof. The curing agents may here not only be included stoichiometrically in the curing reaction, but may also be catalytically active. Examples of substituted guanidines are methylguanidine, dimethylguanidine, trimethylguanidine, tetramethylguanidine, methylisobiguanidine, dimethylisobisguanidine, tetramethylisobiguanidine, hexamethylisobiguanidine, heptamethylisobiguanidine and cyanoguanidine. Examples of suitable melamine resins are methoxymethylmethyloleamine, hexamethoxymethylmelamine, methoxymethylmelamine, hexamethoxymethylmelamine. Examples of suitable guanamine derivatives which may be mentioned are alkylated benzoguanamine resins, benzoguanamine resins or methoxymethylmethoxybenzoguanamine.

Examples of catalytically active substituted ureas are in particular p-chlorophenyl-N,N-dimethylurea (Monuron) or 3,4-dichlorophenyl-N,N-dimethylurea (Diuron). Examples of catalytically active tertiary alkylamines are tris(dimethylaminomethyl)phenol, piperidine and derivatives thereof, diethanolamines and various imidazole derivatives. Representatives of the many useable imidazole derivatives which may be mentioned are: 2-ethyl-4-methylimidazole (EMI), N-butylimidazole, benzimidazole, N-C<sub>1-12</sub>alkylimidazoles. Further examples of tertiary amine derivatives are aminooxadiazole, tertiary amine oxides, diaza aromatic tertiary amines, such as methylpyrazines, diallyltetrahydropyridyl and hydrogenated pyridine bases. Less reactive diamines may furthermore be present as a curing agent component, in particular aromatic diamines, such as diaminodiphenyl sulfone, 4,4'-methylene dianiline, m-phenylene diamine or also polyoxyalkylene polyamines of the "Jeffamine" type and similar diamines.

Blocked polyurethane resins for the purposes of the present invention are di- or polyisocyanate compounds, which are obtained in a manner known *per se* by reacting aliphatic, alicyclic or aromatic isocyanates having at least 2 isocyanate groups per molecule with polyols, wherein in this first stage the isocyanate groups are used in stoichiometric excess relative to the alcohol groups. In a subsequent stage, the remaining isocyanate groups are then reacted in a known manner with blocking agents for the isocyanate groups. Examples of isocyanates which may be mentioned are: m-phenylene diisocyanate, p-phenylene diisocyanate, 2,4-tolylene diisocyanate (TDI), 2,6-tolylene diisocyanate (TDI), p-xylene diisocyanate, diphenylmethane diisocyanate (MDI), hexamethylene diisocyanate, dimeric acid diisocyanate, 1-isocyanatomethyl-3-isocyanato-1,5,5-trimethylcyclohexane (IPDI), hydrogenated MDI (H<sub>12</sub>MDI), tetramethylxylene diisocyanate (TMXDI), the biuretisation product of hexamethylene diisocyanate, the isocyanuratisation product of hexamethylene diisocyanate and the isocyanuratisation product of IPDI.

Dihydric alcohols, such as ethylene glycol, propylene glycol, butanediol, hexanediol, and the hydroxy-functional reaction products thereof with dicarboxylic acids (polyester polyols) or the alkoxylation products thereof with ethylene oxide and/or propylene oxide or mixtures thereof



(polyether polyols) may be used as the polyol. The above-stated dihydric alcohols may here be entirely or partially replaced by trihydric starter alcohols, such as glycerol or trimethylolpropane, or tetrahydric alcohols, such as pentaerythritol.

Hydroxy-functional acrylate and/or methacrylate homo- or co-polymers may also be used as the polyol component.

Any known blocking agents may be used as the blocking agent (protective group) for the isocyanate groups remaining after the reaction of the polyisocyanate with the polyol, the following being mentioned by way of example, lower aliphatic monoalcohols, such as methanol, ethanol, propanol, butanol or octyl alcohol, together with monoethers of ethylene glycol and/or diethylene glycol, aromatic hydroxy compounds, such as phenol, alkylphenols or (alkyl)cresols. Oximes, such as acetone oxime, methyl ethyl ketone oxime and the like, may also be used as a blocking agent. Lactam blocking agents which may be mentioned are  $\epsilon$ -caprolactam, while CH-acidic  $\beta$ -dicarbonyl compounds, such as malonic esters, may also be considered as blocking agents.

Particularly preferred organic binders are those which contain a blocked polyurethane resin based on the more highly reactive aromatic polyisocyanates, in particular MDI, blended with a blocked polyurethane resin based on aliphatic polyisocyanates, in particular IDPI or TMXDI.

The anti-corrosive composition additionally contains 0 to 30wt% of a solvent or solvent mixture, wherein a proportion of this solvent or solvent mixture may already be introduced by the epoxy resin component or polyurethane resin component, in particular if conventional commercial binder components are used for this purpose. Suitable solvents are any solvents conventional in the lacquer industry based on ketones, such as methyl ethyl ketone, methyl isobutyl ketone, methyl n-amyl ketone, ethyl amyl ketone, acetylacetone, diacetone alcohol. Aromatic hydrocarbons, such as toluene, xylene or mixtures thereof, may also be used, as may aliphatic hydrocarbon mixtures having boiling points between about 80 and 180°C. Further suitable solvents are, for example, esters, such as ethyl acetate, n-butyl acetate, isobutyl isobutyrate, or alkoxyalkyl acetates, such as methoxypropyl acetate or 2-ethoxyethyl acetate. Monofunctional alcohols, such as isopropyl alcohol, n-butanol, methyl isobutyl carbinol or 2-ethoxyethanol, or monoalkyl ethers of ethylene glycol, diethylene glycol or propylene glycol may also be mentioned as representatives of many suitable solvents. It may be convenient to use mixtures of the above-stated solvents.

The conductive and weldable anti-corrosive composition furthermore contains finely divided conductive extenders in quantities of between 40 and 70wt%. Powdered zinc, powdered aluminium, graphite and/or molybdenum disulfide, carbon black, iron phosphide or BaSO<sub>4</sub> doped with tin or antimony may be mentioned by way of example.

0 to 15wt% of silicate-based anti-corrosive pigments may additionally be used. Such anti-corrosive pigments are known and zinc/calcium/aluminium/strontium polyphosphate silicate hydrate, zinc/boron/tungsten silicate, doped SiO<sub>2</sub> may be mentioned by way of example.

Familiar known additives, such as lubricants, soluble dyes or colouring pigments, together with wetting agents and levelling auxiliaries, may also be used.

The conductive, weldable anti-corrosive compositions according to the present invention are in particular suitable for coating sheet metal using the coil coating process. To this end, the sheet metal



is initially subjected to conventional pretreatment processes, such as cleaning and degreasing. Conventional phosphating processes and chromating processes may optionally subsequently be performed. A particular advantage of the anti-corrosive compositions according to the present invention is that chromium-free pretreatment processes may also be used with success.

5 After the pretreatment, coating with the anti-corrosive composition according to the present invention is performed using a conventional coil coating process. Film thicknesses (dry film thicknesses) of 1 to 10µm, in particular of 2 to 5µm are particularly preferred. The organic coating is stoved at temperatures of between 160°C and 260°C peak metal temperature (PMT), preferably between 180°C and 235°C PMT.

10 The following Examples are intended to illustrate the present invention in greater detail. Unless otherwise indicated, all quantities in the compositions are stated as parts, by weight.

The compositions listed in Table 1 according to Examples 1 to 10 are produced by mixing together the binder, curing agent, extenders, pigments, solvents and additives. A proportion of the solvent was here already introduced into the composition with the solvent-borne polyurethane binder or curing agent. Mixing was performed in mixing units conventional in the lacquer sector (high speed stirrers) until a homogeneous composition was obtained.

15 0.8mm thick sheet steel (ZE 50/50) was provided in a conventional manner with no-rinse chromating using "Granodine 4513" (Henkel) and then coated with the organic conductive coatings according to the present invention such that a dry film thickness of about 3µm was obtained. The stoving temperature was about 215°C PMT. The sheet metal coated in this manner was then provided with a conventional cathodic electrocoating, whereupon this coating was fully cured according to the prior art.

20 As is evident from the test results in Table 2, all the coatings according to the present invention have an excellent anti-corrosive action. The organic coatings according to the present invention are moreover sufficiently resistant to conventional solvents (methyl ethyl ketone), as is evident from the MEK test.

25 In comparative tests, the adhesion performance of the present composition according to Example 11 was compared with a prior art composition. As is clear from the test results in Table 3, both the compositions according to the present invention and the prior art comparison composition have a good anti-corrosive action, provided that the coated substrates are not subjected to mechanical stress. The substrates in the tests according to Table 3 were pretreated in a similar manner to that described above by no-rinse chromating, wherein phosphating was omitted. Since the adhesion performance of these coatings was to be tested, a cathodic electrocoating was not applied. As is evident from the results in Table 3, the coating according to the present invention according to 30 Example 11 is distinctly superior to the prior art both under impact loading (reverse impact) and in flexural testing (T-bend) and in abrasion testing.







301001 18043

7

Table 1:

Example	1	2	3	4	5	6	7	8	9	10
PUR binders										
Blocked polyurethane based on TDI polyesterol	6.5	0	0	6.5	0	6.5	0	6.5	0	7
Blocked polyurethane based on IPDI polyesterol	0	5	0	0	0	0	5	0	6.5	0
Blocked polyurethane based on HDI polyesterol	0	0	0	0	8	0	4	0	0	5
Blocked polyurethane based on MDI polyesterol	0	5.3	7	0	0	0	0	0	9	0
Bisphenol A based epoxy resin	5.5	2.5	4	5.5	5	6	5	5.5	0	4
Curing agents										
Cyanoguanidine	1	1.5	0	0	0	1	0	0	0	1
Hexamethoxymethylmelamine	0	0	2	0	0	0	3	0	0	0
Benzoguanamine	0	0	0	0	5	0	0	5	0	0
Polyoxyalkylenetriamines	0	0	0	2	0	0	0	0	2	0
Conductive extenders/pigments										
Zinc powder	50	60	50	60	50	60	40	40	35	35
Carbon black	0	0.2	0	0	0	0	0	0	0	0
Aluminium flake	0	0	0	0	5	0	5	5	0	0
Molybdenum disulfide	1.5	0	2.5	0	0	0	0	0	0	0
Iron phosphide	0	0	0	0	0	0	0	0	20	15
SnO/SbO doped barium sulfate	0	0	0	0	0.5	5	0	0	0	0
Anti-corrosive pigments										
Zn/Ca/Al/Sr polyphosphate silicate hydrate	0	0	3	5.5	0	0	6	0	0	0
Zinc/boron/tungsten silicate	0	0	4	0	2	0	0	0	0	5
Doped silica	6	6	2	0	0	0	0	6	5	0
Solvents										
1-Methoxy-2-propyl acetate	7	6	5	5	7	7	10	10	9	8
Diacetone alcohol	5	5	10	7	5	5	7	7	5	6
Solvesso 200	3	0	0	0	0	9	5	5	3	5
Solvesso 100	14	0	0	0	2	0	0	0	5.5	0
Solvesso 150	0	8	10	8	10	0	10	10	0	9
Additives										
Phthalocyanine pigment	0.1	0	0	0	0	0.2	0	0	0	0
Modified castor oil	0.2	0.3	0.2	0.2	0.2	0.3	0	0	0	0
Dispersion auxiliary	0.2	0.2	0.3	0.3	0.3	0	0	0	0	0
Total	100	100	100	100	100	100	100	100	100	100



30001 1543

8

Table 2: Test results

Example	1	2	3	4	5	6	7	8	9	10
Pigment/binder ratio	4.4	4.6	4.7	4.7	3.2	4.8	3.0	3.0	3.4	3.2
Solids content (wt%)	71	81	75	80	76	79	68	68	77.5	72
Binder content (wt%)	13	14.3	13	14	18	13.5	17	17	17.5	17
Red rust in flange <sup>1)</sup>	0	0	0	0	0	0	0	0	0	0
Creepage <sup>2)</sup>	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm	<1.5mm
MEK test <sup>3)</sup>	>10DH	>10DH	>10DH	>10DH	>10DH	>10DH	>10DH	>10DH	>10DH	>10DH

Comments

- 1) After 10 cycles, VDA 621-416, evaluation in accordance with Daimler-Benz specification.
- 2) After 10 cycles, VDA 621-415, evaluation similar to DIN 53167
- 3) Pursuant to DIN 53339, DH = to-&-fro stroke, not cathodically electrocoated.

5

Table 3: Comparative tests

Example	11	Comp.
Blocked polyurethane based on TDI polyesterol	10.5	6.5
Bisphenol A based epoxy resin	2.5	5.5
Cyanoguanidine	1	0
Zinc powder	50.5	50.5
Molybdenum disulfide	2	2
Doped silica	6	6
1-Methoxy-2-propyl acetate	8	8
Diacetone alcohol	9	8
Solvesso 200	2	2
Solvesso 100	0	11
Solvesso 150	8	0
Phthalocyanine pigment	0.1	0.1
Modified castor oil	0.2	0.2
Dispersion auxiliary	0.2	0.2
Total	100	100
Reverse impact (2 kg/m) <sup>1)</sup>	0	3
MEK test, to-&-fro strokes <sup>2)</sup>	>10	>10
T-bend at t = 0 <sup>3)</sup>	1	3
Abrasion (g/m <sup>2</sup> on bowl) <sup>4)</sup>	1	2.5
SS test to red rust <sup>5)</sup>	>600 h	>600 h

## Notes

- 1) According to ECCA T 6, evaluation scale to DIN 53230 where 0 = best value and 5 = very poor.
- 2) Pursuant to DIN 53339.
- 3) According to ECCA T 20 (mandrel bending test with bending radius t = 0 mm), evaluation to DIN 53230.
- 4) A bowl-shaped indentation was drawn in sheet metal provided with the cured coating and the missing quantity of coating determined.
- 5) Salt spray test to DIN 53167, evaluation to DIN 50021.



**The claims defining the invention are as follows:**

1. A conductive and weldable anti-corrosive coating composition for coating metal surfaces, comprising: (a) 10 to 40wt% of an organic binder containing: (aa) at least one epoxy resin; (ab) at least one curing agent selected from guanidine, substituted guanidines, substituted ureas, melamine resins, guanamine derivatives, cyclic tertiary amines and mixtures thereof; (ac) at least one blocked polyurethane resin; (b) 0 to 15wt% of a silicate-based anti-corrosive pigment; (c) 40 to 70wt% of powdered zinc, aluminium, graphite, molybdenum disulfide, carbon black, iron phosphide, and/or barium sulfate doped with tin or antimony; (d) 0 to 30wt% of a solvent.
2. A composition as claimed in claim 1, wherein at least one epoxy based on bisphenol A glycidyl ether and having a molecular weight of at least 800 is used as the epoxy resin.
3. A composition as claimed in claim 1 or claim 2, wherein the substituted guanidines used are methylguanidine, dimethylguanidine, tetramethylguanidine, methylisobiguanidine, tetramethylisobiguanidine, heptamethylisobiguanidine, cyanoguanidine, the substituted urea is N'-dichlorophenyl-N,N-dimethylurea, N'-chlorophenyl-N,N-dimethylurea, and/or the cyclic tertiary amine used is imidazole, alkyl- or arylimidazoles.
4. A composition as claimed in any one of claims 1 to 3, wherein the polyurethane resin used comprises one or more polyester prepolymers based on aromatic and/or aliphatic di- or polyisocyanates, the isocyanate end groups being blocked by known blocking agents.
5. A conductive and weldable anti-corrosive coating composition for coating metal surfaces, said coating composition being substantially as hereinbefore described with reference to any one of the examples, but excluding the comparative examples.
6. Use of a composition as claimed in any one of the preceding claims for coating sheet metal in the coil coating process.
7. A process for coating metal surfaces with a conductive organic anti-corrosive layer, characterised by the following stages:
  - conventional pretreatment consisting of
  - cleaning
  - optional phosphating
  - optional chromating
  - optional chromium-free pretreatment
  - coating with a composition as claimed in any one of claims 1 to 5 to a film thickness of 1 to 10µm,
  - stoving of the organic coating at temperatures of between 160 and 260°C peak metal temperature (PMT).
8. A process as claimed in claim 7, wherein the film thickness is between 2 and 5µm.
9. A process as claimed in claim 7 or claim 8, wherein the metal surfaces are iron (sheet steel), galvanised and alloy-galvanised steels, aluminium or magnesium.



10. A process for coating metal surfaces with a conductive organic anti-corrosive layer, said process being substantially as hereinbefore described with reference to any one of the examples, but excluding the comparative examples.

Dated 29 October 2001

HENKEL KOMMANDITGESELLSCHAFT AUF AKTIEN

5

Patent Attorneys for the Applicant/Nominated Person  
SPRUSON & FERGUSON

3  
5  
7  
9  
11  
13  
15  
17  
19  
21  
23  
25  
27  
29  
31  
33  
35  
37  
39  
41  
43  
45  
47  
49  
51  
53  
55  
57  
59  
61  
63  
65  
67  
69  
71  
73  
75  
77  
79  
81  
83  
85  
87  
89  
91  
93  
95  
97  
99  
101  
103  
105  
107  
109  
111  
113  
115  
117  
119  
121  
123  
125  
127  
129  
131  
133  
135  
137  
139  
141  
143  
145  
147  
149  
151  
153  
155  
157  
159  
161  
163  
165  
167  
169  
171  
173  
175  
177  
179  
181  
183  
185  
187  
189  
191  
193  
195  
197  
199  
201  
203  
205  
207  
209  
211  
213  
215  
217  
219  
221  
223  
225  
227  
229  
231  
233  
235  
237  
239  
241  
243  
245  
247  
249  
251  
253  
255  
257  
259  
261  
263  
265  
267  
269  
271  
273  
275  
277  
279  
281  
283  
285  
287  
289  
291  
293  
295  
297  
299  
301  
303  
305  
307  
309  
311  
313  
315  
317  
319  
321  
323  
325  
327  
329  
331  
333  
335  
337  
339  
341  
343  
345  
347  
349  
351  
353  
355  
357  
359  
361  
363  
365  
367  
369  
371  
373  
375  
377  
379  
381  
383  
385  
387  
389  
391  
393  
395  
397  
399  
401  
403  
405  
407  
409  
411  
413  
415  
417  
419  
421  
423  
425  
427  
429  
431  
433  
435  
437  
439  
441  
443  
445  
447  
449  
451  
453  
455  
457  
459  
461  
463  
465  
467  
469  
471  
473  
475  
477  
479  
481  
483  
485  
487  
489  
491  
493  
495  
497  
499  
501  
503  
505  
507  
509  
511  
513  
515  
517  
519  
521  
523  
525  
527  
529  
531  
533  
535  
537  
539  
541  
543  
545  
547  
549  
551  
553  
555  
557  
559  
561  
563  
565  
567  
569  
571  
573  
575  
577  
579  
581  
583  
585  
587  
589  
591  
593  
595  
597  
599  
601  
603  
605  
607  
609  
611  
613  
615  
617  
619  
621  
623  
625  
627  
629  
631  
633  
635  
637  
639  
641  
643  
645  
647  
649  
651  
653  
655  
657  
659  
661  
663  
665  
667  
669  
671  
673  
675  
677  
679  
681  
683  
685  
687  
689  
691  
693  
695  
697  
699  
701  
703  
705  
707  
709  
711  
713  
715  
717  
719  
721  
723  
725  
727  
729  
731  
733  
735  
737  
739  
741  
743  
745  
747  
749  
751  
753  
755  
757  
759  
761  
763  
765  
767  
769  
771  
773  
775  
777  
779  
781  
783  
785  
787  
789  
791  
793  
795  
797  
799  
801  
803  
805  
807  
809  
811  
813  
815  
817  
819  
821  
823  
825  
827  
829  
831  
833  
835  
837  
839  
841  
843  
845  
847  
849  
851  
853  
855  
857  
859  
861  
863  
865  
867  
869  
871  
873  
875  
877  
879  
881  
883  
885  
887  
889  
891  
893  
895  
897  
899  
901  
903  
905  
907  
909  
911  
913  
915  
917  
919  
921  
923  
925  
927  
929  
931  
933  
935  
937  
939  
941  
943  
945  
947  
949  
951  
953  
955  
957  
959  
961  
963  
965  
967  
969  
971  
973  
975  
977  
979  
981  
983  
985  
987  
989  
991  
993  
995  
997  
999



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**